

Gas/Petrol Duo Pump | SR 20 PC 2 CORE

Specifications

article number		158.152.178
model		SR 20 PC 2 CORE
equipped with (connector type)		CORE
max. working pressure	psi	10443
short description		Gas/Petrol Duo Pump
number of stages		3
first stage output / min.	oz	98.1
second stage output / min.	oz	44
third stage pressure range min.	psi	4061
third stage pressure range max.	psi	10443
third stage output / min.	oz	18.6
capacity fuel tank	oz	57.5
continuous operation	hrs	3.5
sound emission (acc. to EN 13204)	dB(A)	85
sound emission (unloaded)	dB(A)	81
capacity oil tank	oz	146.8
capacity oil tank (effective)	oz	135.3
operator type		petrol engine
number of tool connections		2
number of tools simultaneously usable		2
pump type		2 x 3-stage axial pump
hydraulic oil type		ISO-L HV VG 15/22
engine		4-stroke - 3.0 HP - 2.2 kW
weight, ready for use	lb	50.0
dimensions (LxWxH)	in	17.9 x 12.4 x 18.1
temperature range	°F	-4 + 131
EN 13204 classification		MTO
NFPA 1936 compliant		yes



Standard supplied with

- Hydraulic oil level indicator

Accessories

CORE Elbow Connector	150.182.176
Quick Fix And Release Bracket	150.062.188
LED Light Spider Range	590.000.343
Mounting Plate Pump Side SR 20	150.062.190
Angled Mounting Plate Truck Side	150.062.193